

TEST REPORT

240295 / 10

Date received: 27/10/17

Date of test: 02/11/17

Date of issue: 16/11/17

Sample name: DV804-E-PLACE series



DVO S.P.A.
VIA XX SETTEMBRE, 272-C.P. N. 65
33080 ROVEREDO IN PIANO (PN)
ITALIA

Deflection of table tops EN 1730:2012, clause 6.7

Worktop dimensions	1600 x 800 x 18 mm	
Distance between supports (span)	1355 mm	
Maximum under load deflection allowed	6,8 mm	5‰ of span

Test results:

Load kg/dm ²	Load on the worktop kg	Load application time days	Under load deflection mm
1,5	192	7	2,55

Note:

- Maximum under load deflection allowed according to UNI 8594:2004
- Load according to clause A.2 Annex A of EN 527-2:2016

Unless otherwise specified, measurement uncertainties expanded to a confidence level of about 95% are $\pm 0,1$ mm for linear measures.

The measurement uncertainties stated in this document have been determined according to UNI CEI 70098-3:2016. They were estimated as expanded uncertainty obtained multiplying the standard uncertainty by the coverage factor k corresponding to a confidence level of about 95%. Normally k=2.

This document is validated by digital signature and time stamping in accordance with the Italian laws and the European Directives which regulate the electronic signature systems.

Managing Director
Dr. Andrea Glavon

The sample name and, when relevant, its description, are given by the orderer, and CATAS does not assume responsibility on this matter. This test report relates to the sample submitted for the test and no others. Additions, deletions or alterations are not permitted. This test report must always be reproduced in its entirety. Unless otherwise stated, sampling has been carried out by the orderer.